

NOVA Customer Help Line 1-800-557-6682

www.novamedicalproducts.com P.O. Box 3039 • Gardena CA 90247





- 300lb Weight Capacity
- Stands with Quad Tip



OR INCIDENTAL DAMAGES WHATSOEVER.

AND FITNESS FOR A PARTICULAR PURPOSE. NOVA SHALL NOT BE LIABLE FOR ANY SEQUENTIAL IMBLIED WARRANTIES, IF ANY, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY THIS FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES,

casters, and other parts subject to normal "wear and tear."

shall not extend to nondurable components, including but not limited to rubber tips, hand grips, This warranty does not cover problems due to user negligence or misuse of the product. This warranty

broducts to our office without prior consent.

your dealer you will also be required to provide a receipt of your purchase. DO NOI return any prepared to indicate the nature of the defect, the product serial number, and the name and location of event that you do not receive satisfactory service, please call us directly at the number below. Be For warranty service, please contact the dealer from whom you purchased your NOVA product. In the

lifetime Limited Warranty represents our confidence in the materials and workmanship of our aervice. This product was built to precise standards and thoroughly inspected prior to shipment. This MOVA stands firm on our commitment to providing the highest quality products, as well as exceptional

incurred in replacement or repair of this product.

defective, it will be repaired or replaced at NOVA's option. This warranty does not cover shipping costs lifetime from date of purchase. If within the specified warranty period, this product is proven to be MOVA Inc. warrants this product to be free from detects in material or workmanship for a period of

Lifetime Limited Warranty

How to Adjust Your SugarCane[™]

- 1. Loosen the anti-rattle knob to allow the base of the cane to be adjusted to the desired position. (Do not completely unscrew)
- 2. Depress the brass knob release that is visible in the series of holes for vertical height adjustment.
- 3. Lengthen or shorten cane to desired height.
- 4. Allow brass knob to pop back out to maintain desired height.
- 5. Tighten anti-rattle knob.

How to Fit a SugarCane

1. Wear your regular walking shoes.

2. The top of the cane should be even with the break in your wrist and/or your hip joint.

3. Place the cane 6" in front of you and 6" over to the side. Your elbow should be bent at a 20 to 30 degree angle.



How to Walk with a SugarCane[®]

- 1. Use the cane in the hand of the opposite side of your injured or weaker lea.
- 2. Stand in a triangular position. Place your good foot behind vour body and your weak or injured foot in front of you opposite of the cane, forming the three points of a triangle. The toe of your weak/injured foot should line up with the cane.

3. Move the good foot first to the front of your body and maintain a triangular position. Then move your weak/injured foot and the cane together in front of your good foot. Make sure that all four tips meets the floor flatly.

4. Take short steps to maintain your balance.



Client: Nova

Job: SugarCane Guide

Trim: 11"w x 7"h

Fold: 2.25"w x 3.5"h

Bleed: .125"

Color:

side A: 4-color process

side b: 4-color process

Contact: Tim Kimble 425 313 9076

tim@kimbledesign.com